

Soundtube XT850-GN 8-in COAXIAL OUTDOOR SPEAKER/Granite green

System Type	8" coaxial outdoor (64 Watt transformer for 25/70.7/100 Volt or 4 Ohm transformer bypass position)
Impedance (nominal)	4 Ohms (nominal)
Sensitivity dB @ 2.38 V/1 m3	88.0 dB
Sensitivity dB @ 1W/1 m	85.0 c!B
Frequency Response (- 3 dB)1	51 Hz-10 kHz
Frequency Response (-10 dB)'	38 Hz - 22 <Hz
Max. Program Power	200 Watts
Max. Continuous Power RMS2	100 Watts
Max. SPL dB @ 1 M	105.0 dB
Coverage Angle (-6 dB @ 2 kHz)	360° Horizontal - 403 Vertical
Coverage Angle (-6 dB <§> 10 kHz)	360° Horizontal - 40° Vertical
Tap Selector	5-Position rotary switch with transformer bypass position
Transducer- Low-Frequency Driver	1 x 203 mm (8.0 in) Polypropylene cone, butyl rubber surround
Transducer- High-Frequency Driver	1 x 25 mm (1.0 in) Aluminum dome
Low-Frequency Voice Coil	32 mm (1.20 in]
Network Type- Low Pass	6 dB per octave, 1 st order
Network Type- High Pass	6 db per octave, 1 st order
Crossover Frequency	3.0 kHz
Enclosure Material	Roto-molded polyethylene plastic
Grille	Stainless-steel with powder-coat finish
Inputs	18-Gauge wire lead
Color Options	Granite green or sandstone
Diameter	360 mm (14.17 in)
Total Height	41/.1 mm (16.42 in)
Weight	7.6 kG (16.7 lbs)
Shipping Weight	10 kG (22 lbs)
Included Accessories	Anti-theft brackets, water-tight strain relief
Optional Accessories	N/A
Packaging	1 Per box
Regulatory- UL	1480 (UEAY) pending
Regulatory- CE	approved
Regulatory- IP	IP55 approved
RoHS	Approved