## Soundsphere SS-110 Page-WH 6.5-in Full-Range for Paging Speaker/300Hz-5kHz/White

System Type	6-1/2" (165 mm) full-range driver
Impedance (nominal)1	4 ohms
Sensitivity dB@ 2.83 V/l m	101 dB (measured from 300 Hz - 3 KHz)
Sensitivity dB @ 1 W/l m 2	98 dB {measured from 300 Hz - 3 kHz)
Frequency Response (- 3 dB)3	500 Hz - 5.5 kHz
Frequency Response (-10 dB) 3	150 Hz-11 kHz
Max. Continuous Peak Power4	120 W
Max. Continuous Power RMS5	60 W
Max. Power SPL @ 1 m 6	116 dB
Coverage Angle (±6 dB @ 500 Hz)	180°
Coverage Angle (±6 dB @ 4 kHz)	100°
Coverage Angle (±6 dB Avg. 500 Hz - 4 kHz)	150°
Transformer	Optional 60 W- planned
Transducer - Low-Frequency Driver	6-1/2" (165 mm) treated pulp fiber
Low-Frequency Voice Coil	1"{25.4 mm)
Enclosure & Reflector Material	Structural foam polystyrene with rustproof hardware
Inputs	Hard-wire leads
Colors	White (paintable); custom colors available
Height	11-7/8" (302 mm)
Diameter	Sphere: 10" (254 mm)
	Reflector: 14-7/8" {378 mm)
Weight	8 lbs. (3.6 kg)
Shipping Weight	11 lbs. (5 kg)
Packaging	One per box