

Rockustics EconoRock-G/T 6.5 inch Coax Outdoor Speaker with Transformer/70W/Gray

System Type	6.5" coaxial, two-way outdoor speaker (optional 64 Watt transformer available)
Impedance (nominal)	4 Ohms (nominal)
Sensitivity dB @ 2.38 V/1 m	90 dB
Sensitivity dB @ 1W/1m ²	87 dB
Frequency Response (- 3 dB) ³	100 Hz- 16 kHz
Frequency Response (-10 dB) ³	76 Hz - 22 kHz
Max. Program Power ¹	140 W
Max. Continuous Power RMS ⁵	70 W
Max. Power SPL @ 1 m ⁶	105.5 db
Directivity Factor (Q)	3.1 (averaged 100 Hz - 10 kHz); 3.7 dB (2 kHz)
Directivity Index (DI)	4.2 (averaged 100 Hz - 10 kHz); 5.7 dB (2 kHz)
Coverage Angle (-6 dB @ 2 kHz)	135°
Coverage Angle (-6 dB @ 10 kHz)	115°
Coverage Angle (Ave from 2 to 10 kHz)	105°
Transducer- Low-Frequency Driver	165 mm (6.5 in.) weather resistant
Transducer- High-Frequency Driver	25 mm (1.0 in.) weather resistant
Low-Frequency Voice Coil	25 mm (1.0 in.)
Enclosure Material	Elastomer reinforced polymer with pulverised stone
Inputs	Wire lead
Color Options	Gray
Width	266.7 mm (10.5 in.)
Height	317.5 mm (12.5 in.)
Depth	266.7 mm (10.5 in.)
Weight	6.8 kg (15 lbs.)
Included Accessories	N/A
Optional Accessories	64 Watt transformer
Packaging	1 Per box