

Rockustics EconoRock-S 6.5in Coax Outdoor Speaker/56Hz-20kHz/70W/Sandstone

| | |
|--|--|
| System Type | 6.5" coaxial, two-way outdoor speaker (optional 64 Watt transformer available) |
| Impedance (nominal) | 4 Ohms (nominal) |
| Sensitivity dB @ 2.38 V/1 m | 90 dB |
| Sensitivity dB @ 1W/1m ² | 87 dB |
| Frequency Response (- 3 dB) ³ | 100 Hz- 16 kHz |
| Frequency Response (-10 dB) ³ | 76 Hz - 22 kHz |
| Max. Program Power ¹ | 140 W |
| Max. Continuous Power RMS ⁵ | 70 W |
| Max. Power SPL @ 1 m ⁶ | 105.5 db |
| Directivity Factor (Q) | 3.1 (averaged 100 Hz - 10 kHz); 3.7 dB (2 kHz) |
| Directivity Index (DI) | 4.2 (averaged 100 Hz - 10 kHz); 5.7 dB (2 kHz) |
| Coverage Angle (-6 dB @ 2 kHz) | 135° |
| Coverage Angle (-6 dB @ 10 kHz) | 115° |
| Coverage Angle (Ave from 2 to 10 kHz) | 105° |
| Transducer- Low-Frequency Driver | 165 mm (6.5 in.) weather resistant |
| Transducer- High-Frequency Driver | 25 mm (1.0 in.) weather resistant |
| Low-Frequency Voice Coil | 25 mm (1.0 in.) |
| Enclosure Material | Elastomer reinforced polymer with pulverised stone |
| Inputs | Wire lead |
| Color Options | Sandstone |
| Width | 266.7 mm (10.5 in.) |
| Height | 317.5 mm (12.5 in.) |
| Depth | 266.7 mm (10.5 in.) |
| Weight | 6.8 kg (15 lbs.) |
| Included Accessories | N/A |
| Optional Accessories | 64 Watt transformer |
| Packaging | 1 Per box |