

Rockustics OctoRock-S 8in Coax Outdoor Speaker/55Hz-20Hz/100W/Sandstone

System Type	8.0" coaxial, two-way, outdoor speaker (optional 64 Watt transformer available)
Impedance (nominal) ¹	4 Ohms (nominal)
Sensitivity dB @ 2.38 V/1 m	90 dB
Sensitivity dB @ 1 W/1m ²	87 dB
Frequency Response (-3 dB) ³	96 Hz- 18kHz
Frequency Response (-10 dB) ³	71 Hz - 22 kHz
Max. Program Power ¹	200 W
Max. Continuous Power RMS ⁵	100 W
Max. Power SPL @ 1 m ⁶	107.0 db
Directivity Factor (Q)	3.0 (averaged 100 Hz - 10 kHz); 4.9 dB (2 kHz)
Directivity Index (pi)	4.1 (averaged 100 Hz - 10 kHz); 6.9 dB (2 kHz)
Coverage Angle (-6 dB @ 2 kHz)	95°
Coverage Angle (-6 dB @ 10 kHz)	105°
Transducer- Low-Frequency Driver	203.2 mm (8.0 in) weather resistant
Transducer- High-Frequency Driver	25 mm (1.0 in.) weather resistant
Low-Frequency Voice Coil	38.1 mm (1.5 in)
Enclosure Material	Elastomer reinforced polymer with pulverised stone
Inputs	Wire lead
Color Options	Sandstone
Width	406.4 mm (16 in.)
Height	311.2 mm (12.25 in.)
Depth	317.5 mm (12.5 in.)
Weight	14.5 kg (32 lbs.)
Included Accessories	N/A
Optional Accessories	64 Watt transformer
Packaging	1 Per box
Regulatory- CE	Approved
RoHS	Approved