

Rockustics PunkRock-S/T 5.25 inch Coax Outdoor Speaker with Transformer/Sandstone

System Type	5.25" coaxial, two-way outdoor speaker (optional 64 Watt transformer available)
Impedance (nominal) ¹	4 Ohms (nominal)
Sensitivity dB @ 2.38 V/1 m	89.0 dB
Sensitivity dB @ 1W/1m ²	86.0 dB
Frequency Response (- 3 dB) ³	118 Hz- 19 kHz
Frequency Response (-10 dB) ³	86 Hz - 22 kHz
Max. Program Power ⁴	150W
Max. Continuous Power RMS ⁵	75 W
Max. Power SPL @ 1 m ⁶	105.0 db
Directivity Factor (Q)	2.5 (averaged 100 Hz - 10 kHz); 3.8 dB (2 kHz)
Directivity Index (DI)	3.2 (averaged 100 Hz - 10 kHz); 5.8 dB (2 kHz)
Coverage Angle (-6 dB @ 2 kHz)	110°
Coverage Angle (-6 dB @ 10 kHz)	100°
Coverage Angle (Ave from 2 to 10 kHz)	120°
Transducer- Low-Frequency Driver	133.35 mm (5.25 in.) weather resistant
Transducer- High-Frequency Driver	25 mm (1.0 in.) weather resistant
Low-Frequency Voice Coil	25 mm (1.0 in.)
Enclosure Material	Elastomer reinforced polymer with pulverised stone
Inputs	Wire lead
Color Options	Brown, gray or sandstone
Height	266.7 mm (10.5 in.)
Width	209.6 mm (8.25 in.)
Depth	241.3 mm (9.5 in.)
Weight	4.98 kg (11 lbs.)
Included Accessories	N/A
Optional Accessories	64 Watt transformer
Packaging	1 Per box