

Video Bandwidth:	600 MHz / 18 Gbps
Input Ports:	(1) HDMI (1) 3.5mm Analog Audio (1) Digital Audio (TOSLINK) (1) USB (Service Only)
Output Ports:	(1) HDMI (1) 3.5mm Analog Audio (1) Digital Audio (TOSLINK)
Output Resolution:	Up to 1080p & WUXGA@60
Analog Audio Input:	Audio Level 2 Vrms Max Impedance 49.9 Kohm Type Unbalanced
Analog Audio Output:	Audio Level 2 Vrms Max THD+N < -80 dB @ 0 dBFS 1 kHz (A-wt) SNR >70 dB @ 0 dBFS Freq. Response < +/- 3 dB @ 20 Hz- 20 kHz Crosstalk < -70 dB @ 10 kHz Type Unbalanced
Optical Audio Input:	Sampling Rate (kHz): 32, 44.1, 48, 82, 88.2, 96, 176.4 and 192
Optical Audio Output:	Sampling Rate: 48 kHz
Mounting:	Brackets at each end with screw holes provided for rack or wall mounting
HDMI Cable Lengths:	Input: 1080p 8-bit: 15m 1080p 12-bit: 10m 4K 8-bit: 3m Output: 1080p 8-bit: 15m 1080p 12-bit: 10m 4K 8-bit: 3m
Power Supply:	100 VAC to 240 VAC, 50-60 Hz, 0.6A, External; 5 VDC, 2.6 A (US/EU Standard, CE/FCC/UL Certified)
Temperature/Humidity:	Storage: -4 to +140 °F (-20 to 60 °C) 20%~90%, non-condensing Operating: +32 to +104 °F (0 to 40 °C) 20%~90%, non-condensing
Typical DC Current Draw:	~2.2 A Max
Enclosure Type:	Metal (Aluminum)
Cooling:	Convection
Dimensions:	4.02" W x 6.5" D x 0.98" H 102 mm W x 165 mm D x 25 mm H
Weight:	Model Only: 0.77 lbs (0.35 kg) each Shipping: 2.85 lbs (1.29 kg)
Safety:	CE
EMI/EMC:	CE, FCC Class A
MTBF:	90,000 hours estimated
Warranty:	3 years parts and labor