

RDL D-PSP1F Decora-Style Active Loudspeaker/White

- **Inputs (2):** 30 k Ω balanced or 10 k Ω unbalanced
- **Input Level:** +4 dBu nominal (Balanced); -10 dBV nominal (Unbalanced)
- **Minimum Input Level:** -18 dBu (Balanced, Max. gain); -19 dBV (Unbalanced, Max. gain)
- **Maximum Input Level:** +22 dBu
- **Gain Adjustment:** Single-turn audio taper (set by installer)
- **Maximum SPL:** 81 dB
- **Frequency Range:** 150 Hz to 20 kHz, nominal
- **CMRR:** > 50 dB (50 Hz to 120 Hz)
- **Power Requirement:** 24 Vdc @ 55 mA (Idle); 100 mA (maximum), Ground-referenced
- **Ambient Operating Environment:** 0° C to 40° C Maximum; 20° C Recommended
- **Dimensions:** Height: 4.12 in. 10.46 cm; Width: 1.72 in. 4.37 cm; Depth: 2.64 in. 6.7 cm
- **Package Type:** Cardboard Box
- **Package Dimensions:** 3.625 x 4.625 x 2.125 in.
- **Shipping Weight:** .573 lbs.
- **WEEE weight:** .435 lbs.
- **Tariff code:** 8518.40.2000