

RDL DB-PA3 3.5 Watt Decora Audio Amplifier/Black

Inputs (2):	20 k Ω balanced or unbalanced bridging
Input Level:	-4 dBu nominal (Balanced, Low input sensitivity); -15 dBV nominal (Unbalanced, High input sensitivity)
Minimum Input Level:	-18 dBu (Balanced, Max. gain); -19 dBV (Unbalanced Mini-Jack, Max. gain)
Maximum Input Level:	+22 dBu (Low input sensitivity); +4 dBu (High input sensitivity)
Gain Adjustment:	Single-turn audio taper (Front-panel)
Output Power:	3.5 W RMS (Max.. into 8 ohms); 6.5 W RMS (Max., into 4 ohms)
Frequency Response:	20 Hz to 20 kHz (\pm 1 dB)
THD+N:	< 0.1% (@ 1 kHz, 1 W)
Noise:	< -80 dB (below 1 W RMS, balanced input); < -70 dB (below 1 W RMS, Mini-Jack input)
CMRR:	> 50 dB (50 Hz tc 120 Hz)
Power Requirement:	24 Vdc @ 30 riA (Idle); 55 -A (1/8 power; normal voice or music); 225 -A (3.5 W into 8 ohms)
Ambient Operating Environment:	0.; C tc 40.; C Maximum; 20° C Recommended
Dimensions:	Height: 4.13 in. 10.49 cm; Width: 1.7 in. 4.32 cm; Depth: 2.05 in. 5.21 cm
Package Type:	Cardboard Box
Package Dimensions:	3.625 x 4.625 x 2.125 in.
Shipping Weight:	.405 lbs.
WEEE weight:	.270 lbs.
Tariff code:	8518.40.2000