

## RDL EZ-HK3 Stereo Audio/Composite Video HUM KILLER

Video Output:	Composite Video, 1 V p-p nominal
Output Impedance:	75 $\Omega$
Video Bandwidth:	40 Hz to >5 MHz
Audio Input:	Stereo on RCA Phono jacks, -10 dBV nominal, ground-isolated
Audio Input Impedance:	10 k $\Omega$
Audio Output:	Stereo on RCA Phono jacks, -10 dBV nominal
Audio Output Impedance:	10 k $\Omega$
Audio Frequency Response:	20 Hz to 20 kHz ( $\pm$ 1 dB)
Audio Total Harmonic Distortion:	<0.05% @ 1 kHz
Crosstalk (channel to channel):	<-75 dB (20 Hz to 10 kHz), <-65 dB (10 kHz to 20 kHz)
Crosstalk (video to audio):	<-80 dB (referred to -10 dBV)
Crosstalk (audio to video):	<-85 dB (referred to 1 V p-p)
Output Ground Isolation:	Switch-selectable (lifts audio and video grounds)
Gain (audio and video):	Unity nominal (passive circuit)
Case dimensions:	2.9" (7.4 cm)W x 3" (7.6 cm)D
Mounting size:	1/6 rack width
Package Type:	Cardboard Box
Package Dimensions:	3.625 x 4.625 x 2.125 in.
Shipping Weight:	0.465 lbs.
WEEE weight:	0.31 lbs.
Tariff code:	8536.90.8085