

## RDL EZ-HSX4 4X1 Stereo Audio Input Switcher with Headphone Amplifier

Inputs (4):	Stereo on dual RCA jacks, > 10 k $\Omega$ , -10 dBV nominal, +10 dBV max.
Level control:	Off to +12 dB gain
Outputs (3):	Stereo on dual RCA jacks (line level, -10 dBV nominal, +10 dBV max. fixed, +17 dBV max. variable), 1/4" (6.3 mm) TRS or Mini jack (2 headphone, 35 mW, 100 $\Omega$ load)
Frequency Response:	10 Hz to 20 kHz (line output $\pm$ 0.05 dB, headphone output $\pm$ 1.25 dB, 100 $\Omega$ load)
THD+N:	< 0.03% (line output), < 0.1% (headphone output, 10 mW, 100 $\Omega$ load)
Crosstalk:	< -70 dB (1 kHz)
Nc:se:	< -100 dB (headphone, below 10 mW output, 100 $\Omega$ load)
Nc:se:	< -80 dB (variable output, below -10 dBV, unity gain), < -95 dB (fixed output, below -10 dBV)
24 Vdc power supply current:	40 mA (idle), 50 mA (max.)
Case dimensions:	5.75" (14.6 cm)W x 5" (12.7 cm)D
Mounting size:	1/3 rack width
Package Type:	Cardboard Box
Package Dimensions:	9.5 x 7 x 2.25 in.
Shipping Weight:	1.215 lbs.
WEEE weight:	0.825 lbs.
Tariff code:	8518.40.2000