

RDL PT-AMG2 Portable Audio Signal Generator and Monitor

| | |
|-------------------------------------|--|
| Outputs (2): | XLR (front-panel selectable mic or line), Phono (consumer level) |
| Balanced Output Level (Selectable): | |
| Line: | +4 dBu or +6 dBu* (2.5 kΩ load) |
| Mic: | -46 dBu (2.5 kΩ load.. 50 dB below +4 dBu) |
| Unbalanced Output Level: | -10 dBV |
| Oscillator Frequency: | 700 Hz nominal |
| Output Stability: | Better than 0.01 dB |
| Inputs (2): | XLR (front-panel selectable mic or line) Phono (consumer level) |
| Balanced Input Level (Selectable): | |
| Line: | +4 dBu or +6 dBu* |
| Mic: | -46 dBu (50 dB below +4 dBu) |
| Unbalanced Input Level: | -10 dBV |
| Reference Level Preset: | Switch-selectable +4 dBu or +6 dBu |
| Ambient Operating Environment: | 0° C to 50° C |
| Power Requirement: | 9 V internal (2) or 12 to 30 Vdc external @ 45 mA |
| Package Type: | Cardboard Box |
| Package Dimensions: | 9.5 x 7 x 2.25 in. |
| Shipping Weight: | 2.3 lbs. |
| WEEE weight: | 1.62 lbs. |
| Tariff code: | 8543.20.0000 |