



M4-EX

POWER CONDITIONER

Noise Filtration/Surge Protection For All Home/Office Equipment

AC Specifications:	
Protect or Disconnect™ Circuitry	Ye
Patented Power Management Circuit*	
Overvoltage Shutoff	144V ±8
Undervoltage Shutoff	90V ±6
Thermal Fusing	
Line Voltage	120VAC, 50/60H
Initial Clamping Level	_200V Peak, 141V RM
Voltage Protection Rating (UL1449 3rd E	dition, 3,000A):500
Protection Modes	L-N, L-G, N-
Maximum Current Rating	15A (1800W
EMI/RFI Noise Filtration	50dB (100kHz - 1 MHz
Response Time	< 1n
Single Pulse Energy Dissipation	1650 Joule
Peak Impulse Current	52,000
General:	· ·
Lightning Protection	Ye
Product Warranty Connected Equipment Protection Policy_	Lifetim

Specifications subject to change without notice due to continuing product updates and improvements

^{*}Patent Pending



1690 Corporate Circle, Petaluma, CA 94954 800-472-5555 • 707-283-5900

www.panamax.com

Designed in U.S.A. Made in China





Model: M4-EX



© 2004 Panamax. The Panamax logo is a registered US trademark of Panamax. Protect or Disconnect is a trademark of Panamax.