

Panamax M4315-PRO 15A Power Conditioner/8 Individually Controlled Outlets

General

Weight	12 lbs.
Rack Ears	Removable
Dimensions	19 in. W (17 in. without rack ears) x 12.25 in. D x 1.75 in H

AC Specifications

Voltage Regulation	No
Total Outlets	9 outlets
Total Current Capacity	15 A (1800W)
Thermal Fusing	Yes
Protection Modes	L-N, L-G, N-G
Peak Impulse Current	135,000
Line Voltage	120VAC, 60 Hz
Isolated Banks	4
Initial Clamping Level	200V Peak, 141V RMS
High Current Outlets	2 outlets
Energy Dissipation	2700 Joules
Catastrophic Srge Circuit	Yes
Auto-resetting Under-voltage shutoff	100 VAC \pm 2 VAC
Auto-resetting Over-voltage shutoff	134 VAC \pm 2 VAC

LAN Protection

Wires Protected	8-wires
Jacks	RJ-45
Compatibility	10/100/1000 BASE-T
Clamping Level	60V \pm 5V

Telco Protection

Suppression Modes	Metallic & Longitudinal
Lines Protected	2-Wire, Pins 4 & 5
Fuseless/Auto-resetting	Yes
Connectors	RJ-11
Clamping Level	260V
Capacitance	30pf (approx.)

Universal Coax Protection

Shielded	Yes
Insertion Loss	< 0.5 dB
HD 1080 i/p Ready	Yes
Frequency Range	0MHz - 2.2 GHz
Connectors	Female "F", Gold Plated
Clamping Level	75V
Bidirectional	Yes

EMI/RFI Noise Filtration

Banks 1,2,3	76db, 5KHz — 250 kHz
Bank 4, High Current Outlets	46 db, 250 KHz — 1 Mhz