

## AVPro Edge AC-MX44-AUHD 18Gbps True 4K/60 AUHD 4x4 Matrix Switch

PRODUCT SPECIFICATIONS	
<b>VIDEO</b>	
HDMI Inputs	4
HDMI Outputs	4
HDMI Output Format	2.0 (a/b)
Video Formats Supported	4K60 (all up to 4:4:4), 4K30, 1080P, 1080I, 720P, 576P, 480P, 576I, 480I
Video Scaling Modes (per output)	Bypass, HDBT Compatiability (9G), 4K->2K, 2K- >4K
HDCP Versions	2.2 and earlier
Signal Rate	18 gbps
HDR Supported	HDR 10, Dolby Vision
<b>AUDIO</b>	
Audio Formats Supported (HDMI)	Up to DTS-HD, Dolby trueHD
SPDIF Audio Outputs	4
Audio Formats SUpported (SPDIF)	Up to Dolby 7.1, DTS, & LPCM
Balanced Audio Outputs	4
Balanced Audio Output level	Line
Audio Delay (per output balanced/SPDIF)	Up to 630MS
<b>OTHER</b>	
EDID Management	SDR & HDR Presets up to 18Gbps (4K 4:4:4), Custom EDIDs, EDID Copy/Emulate
Input Video Signal	0.5-1.0 volts p-p
Input DDC Signal	5 volts p-p
Transmission Distance over HDMI	45 Feet (15 Meters)
Control	RS-232, IR, Ethernet
RS-232 Settings	Baud rate: 57600   Data bits: 8   Parity: None   Stop Bits: 1   Handshaking: None
Power Supply	12V 4A (100-240V input)
Power Consumption	30W (Max)
Operating Temprature	32-95°F (0-35°C)
Operating Humidity	15-90% RH
Weight	5.3LBS
Dimensions	L440 x W256 x H42 mm 17.3 x 10 x 1.65 in 19 inch RU's: 1
*Specifications subject to change without notice. Mass & Dimensions are approximate	