

<b>Connection</b>	8
<b>Connectors</b>	
Serial	8 x RJ-45 Female
LAN Ports	2 x RJ-45 Female
Power	2 x IEC 60320/C14
PON	1 x RJ-45 Female (Reserved)
Modem	1 x RJ-45 Female
Local Console	1 x RJ-45 Female
Laptop USB Console (LUC) Port	1 x Mini USB
USB Port	3 x USB Type A Female
<b>Switches</b>	
Power	2 x Rocker Switch
Reset	1 x Recessed Pushbutton
<b>Maximum Input Power Rating</b>	100-240V~, 1A, 50/60Hz
<b>Power Consumption</b>	AC110V:14.1W:98BTU AC220V:14.0W:98BTU
<b>LEDs</b>	
Serial	8 (Green)
10/100/1000 Mbps	2 (Red / Orange / Green)
Power	2 (Blue)
<b>Mode of Operation</b>	Console Management, <input type="checkbox"/> Console Management Direct, <input type="checkbox"/> Real Com Port, <input type="checkbox"/> TCP Server/Client, <input type="checkbox"/> UDP Server/Client, <input type="checkbox"/> Virtual Modem
<b>Environmental</b>	

Operating Temperature	0 - 40°C
Storage Temperature	-20 ~ 60°C
Humidity	0 - 80% RH, Non-condensing
<b>Physical Properties</b>	
Housing	Metal
Weight	4.45 kg ( 9.8 lb )
Dimensions (L x W x H)	43.72 x 32.98 x 4.40 cm (17.21 x 12.98 x 1.73 in.)
<b>Note</b>	For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format.