

Aten KN1116VA 1-Local/1-Remote Access 16-Port Cat 5 KVM over IP Switch with Virtual Media (1920x1200)

| | |
|-------------------------------|--|
| Console Connections | |
| Local | 1 |
| Remote | 1 |
| Computer Connections | |
| Direct | 16 |
| Maximum | 256 (via Cascade) |
| Port Selection | Pushbuttons, GUI, Hotkeys |
| Connectors | |
| Console Ports | 2 x USB Type-A Female (White) 1 x 6-pin Mini-DIN Female (Purple) 1 x 6-pin Mini-DIN Female (Green) 1 x HDB-15 Female (Blue) |
| USB Port | 3 x USB Type-A Female |
| Audio | 2 x Audio Jack Female |
| Laptop USB Console (LUC) Port | 1 x USB Mini-B Female |
| KVM Ports | 16 x RJ-45 Female |
| Serial | 2 x RJ-45 Female |
| PON | 1 x RJ-45 Female |
| Modem | 1 x RJ-45 Female |
| LAN Ports | 2 x RJ-45 Female |
| Power | 2 x IEC 60320/C14 |
| Switches | |
| Port Selection | 2 x Pushbutton |
| Reset | 1 x Semi-recessed Pushbutton |
| Power | 2 x Rocker |
| LEDs | |
| Online | 16 (Green) |
| Link 10 / 100 / 1000 Mbps | 2 (Red/Orange/Green) |
| Power | 2 (Blue) |
| Emulation | |
| Keyboard / Mouse | PS/2 / USB |
| Video | |
| Local | 1920 x 1200@60 Hz |
| Remote | 1920 x 1200@60 Hz |
| Scan Interval | 1-255 Seconds |
| Maximum Input Power Rating | 100-240V AC, 50-60Hz, 1A |
| Power Consumption | AC110V:16.5W:114BTU AC220V:16W:111BTU |
| Environmental | |
| Operating Temperature | 0 - 50°C |
| Storage Temperature | -20 - 60°C |
| Humidity | 0 - 80% RH, Non-condensing |
| Physical Properties | |
| Housing | Metal |
| Weight | 3.56 kg (7.84 lb) |
| Dimensions (L x W x H) | 43.84 x 28.78 x 4.40 cm (17.26 x 11.33 x 1.73 in.) |
| Note | For some of rack mount products, please note that the standard physical dimensions of WxDxH are expressed using a LxWxH format. |

