

## **VIDEO**

Input: 2x DVI-I (HDMI/DVI/VGA)

Output: N/A

## **AUDIO**

Input: 3.5 mm Stereo Phone Jack

Output: 2x 3.5 mm Stereo Phone Jack

## **MICROPHONE INPUT**

N/A

## **USB**

Tx Side: 2x USB Type B (Female)

Rx Side: N/A

## **SYSTEM LINK**

Input: N/A

Output: 2x RJ45

## **RS-232 BAUD RATE**

3-pin Phoenix connector / up to 115,200 bps / full duplex

## **VIDEO RESOLUTION**

HDMI/VGA: 1920x1080@60Hz, DVI: 1920x1200@60Hz

## **INTERCONNECT CABLE**

Standard CAT6/CAT6a/CAT7 network cable

## **MAXIMUM CABLE LENGTH**

170m point-to-point, 100m when connected to a switch

## **TEMPERATURE**

Operating temperature: 0 ~ 50 C, storage temperature: -20 ~ 85C

## **ENVIRONMENTAL HUMIDITY**

0 ~ 80% (non-condensing)

## **POWER**

DC 12V, 1.5A

Consumption 400 mA

**WEIGHT**

600g

**DIMENSIONS**

153.4 x 88.2 x 63 mm