

Kramer KDS-8 Zero Latency 4K HDR SDVoE Video Streaming Transceiver over Copper

INPUTS

- 1 HDMI: On a female HDMI connector
- 1 IR: On a 3.5mm mini jack

OUTPUTS

- 1 HDMI: On a female HDMI connector
- 1 IR: On a 3.5mm mini jack

PORTS

- 1 10GbE Ethernet: On an R-J45 connector
- 1 Unbalanced Stereo Audio: On a 3.5mm mini jack
- 1 1GbE Ethernet: On an R-J45 connector
- 1 RS-232: On a 3-pin terminal block connector

VIDEO

- Standards Compliance: 10/12-bit HDR (Point-to-Point and Genlock mode only), HDCP 2.2 &1.4, DVI 1.0,

EXTENSION LINE

- Signal Compression: Ultra-light compression, lossless for most content
- Range: Up to 100m in point-to-point mode

AUDIO

- Standards Compliance: Supports pass-through of audio formats including LPCM 2.0/5.1/7.1, Bitstream and HD Bitstream from HDMI sources

POWER

- Source: 12V DC
- Consumption: 3A

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0 to + 45°C (32 to + 113 °F), 10% to 90%, non-condensing
- Storage Temperature: -20 to +70°C (-4 to + 158 °F), 10% to 90%, non-condensing
- Humidity: 10% to 90%, non-condensing

PRODUCT DIMENSION

- 23.10cm x 11.60cm x 2.50cm (9.09" x 4.57" x 0.98") W, D, H

PRODUCT WEIGHT

- 0.5kg (1.1lbs) approx.

SHIPPING DIMENSION

- 35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H

SHIPPING WEIGHT

- 1.2kg (2.6lbs) approx.