

<b>Rated Output:</b>	Constant voltage 70V or 100V @ 40 w max (mono on a captive screw connector)
<b>Gain:</b>	26 dB
<b>Frequency Range:</b>	20 Hz to 20Khz
<b>Signal/Noise Ratio:</b>	80 dB max
<b>Total Harmonic Distortion:</b>	1%@1KHz, 0.3%@20KHz at nominal level
<b>Input Impedance:</b>	> 10 Kohm
<b>Stereo Channel Separation:</b>	>75 dB from 20 Hz to 20 KHz
<b>CMRR:</b>	>70 dB from 20 Hz to 20 KHz
<b>Operating Temperature:</b>	0°C to 40°C (32°F to 104)
<b>Humidity:</b>	20 to 90% non-condensing
<b>Power:</b>	Max Consumption: 40 watts Idle Consumption: 4 watts
<b>Power Supply:</b>	Input: 100 VAC to 240 VAC, 47-63 Hz Output 24 VDC / 5A
<b>Dimension:</b>	Model: 6.0" (153 mm) W x 5.7" (144 mm) D x 1.7" (44 mm) H
<b>Weight:</b>	Model: 2.0 lbs (0.9 kg) Shipping: 4.1 lbs (1.9 kg)
<b>Certifications:</b>	Unit: CE, FCC, RoHS Power Supply: cULus