

Gefen EXT-HD2IRS-LAN-RX HDMI over IP with RS-232 and Bi-Directional IR Receiver

- Maximum Pixel Clock: 165 MHz
- Maximum TMDS Clock: 225 MHz
- Video Input Connector (Sender): (1) HDMI Type A 19-pin, female, locking
- Video Output Connector (Receiver): (1) HDMI Type A 19-pin, female, locking
- RS-232 ports (Sender/Receiver): (1) 3.5mm mini-stereo jack (DB-9 adaptors included)
- IR Emitter ports (Sender/Receiver): (1) 3.5mm mini-mono jack
- IR In/Extender ports (Sender/Receiver): (1) 3.5mm mini-stereo jack
- IR Extender: EXT-RMT-EXTIRN
- Ethernet connectors (Sender/Receiver): (1) RJ-45, shielded
- Reset buttons (Sender/Receiver): (1) tact-type, recessed
- Link Indicator (Sender/Receiver): (1) LED, amber
- Power Indicator (Sender/Receiver): (1) LED, green
- Power Supply (Sender / Receiver): 5V DC, locking
- Power Consumption (Sender): 6W maximum
- Power Consumption (Receiver): 4W maximum
- Operating Temperature: 0 to +50 °C
- Operating Humidity: +10 to +90%, Relative Humidity, non-condensing
- Storage Temperature: -20 to +85 °C
- Storage Humidity: 0 to +95%, Relative Humidity, non-condensing
- MTBF: 50000 hours
- Dimensions (Sender / Receiver) (W x H x D): 4.3 x 1 x 3.2 (110mm x 26mm x 80mm)
- Unit Weight:
 - EXT-HD2IRS-LAN-TX: 0.4 lbs. (0.2 kg)
 - EXT-HD2IRS-LAN-RX: 0.4 lbs. (0.2 kg)
- Shipping Weight:
 - EXT-HD2IRS-LAN-TX: 2.0 lbs. (0.9 kg)
 - EXT-HD2IRS-LAN-RX: 2.0 lbs. (0.9 kg)