

|                         |  |
|-------------------------|--|
| <b>Video Standards:</b> | DVI (single link)<br>HDMI 1.4 video specifications including 12 bit color depth, 3D video<br>HDCP 1.4  |
| <b>Connectors:</b>      | (1) HDMI Input<br>(1) HDMI Output<br>(1) RJ45 Output<br>(1) Mini-USB Service Port<br>(1) 2.0MM Locking DC Power Input                        |
| <b>Resolutions:</b>     | DVI Signal: VGA (640x480) thru WUXGA (1920x1200)<br>HDTV Signal: 480p through 4K60 4:2:0 (Interlaced resolutions are not supported)          |
| <b>Power Supply:</b>    | 100 VAC to 240 VAC, 47-63 Hz, External; 5 VDC  |
| <b>Temp/humidity:</b>   | Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, non-condensing<br>Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, non-condensing |
| <b>Typical DC:</b>      | 5V DC, 4.0 A Power Supply  |
| <b>Current Draw:</b>    | TBD  |
| <b>Cooling:</b>         | Convection   |
| <b>Enclosure type:</b>  | Metal (Steel)  |
| <b>Dimensions:</b>      | TBD  |
| <b>Product weight:</b>  | Model Only<br>TBD  |
|                         | Shipping<br>TBD  |
| <b>Safety:</b>          | CE   |
| <b>EMI/EMC:</b>         | CE, FCC Class A  |
| <b>MTBF:</b>            | 90,000 hours (estimate)  |