

## **Gefen EXT-VGAKVM-LANRX VGA/USB/analog audio/RS-232/IR Extender (Receiver)**

- Maximum Video Bandwidth: 350 MHz
- Video Input Connector (Sender): (1) VGA HD-15, female
- Video Output Connector (Receiver): (1) VGA HD-15, female
- Line Input (Sender): (1) 3.5mm mini-stereo jack
- Line Output (Sender): (1) 3.5mm mini-stereo jack
- Mic Input (Receiver): (1) 3.5mm mini-stereo jack
- Line Output (Receiver): (1) 3.5mm mini-stereo jack
- USB Host Interface (Sender): (1) USB Type B, female
- USB Device Connectors (Receiver): (2) USB Type A, female
- RS-232 Connector (Sender): (1) DB-9, female
- RS-232 Connector (Receiver): (1) DB-9, male
- IR Emitter (Sender): (1) 3.5mm mini-mono jack
- IR Extender (Receiver): (1) 3.5mm mini-stereo jack
- IR Extender Type: EXT-RMT-EXTIRN
- Ethernet connector (Sender): (1) RJ-45, shielded
- Ethernet connectors (Receiver): (3) RJ-45, shielded
- Mode button (Sender): (1) tact-type
- ID Selector switch (Sender): (1) rotary-type
- Switch button (Receiver): (1) tact-type
- Reset button (Receiver): (1) tact-type, recessed
- Link Indicator (Sender/Receiver): (1) LED, green
- Power Indicator (Sender/Receiver): (1) LED, blue
- Power Consumption (Sender / Receiver): 10W (max.)
- Dimensions (Sender / Receiver) (W x H x D): 8.4 x 1.7 x 4.5 (213mm x 43mm x 113mm)