

WyreStorm ENA-001-010 Enado Controller/16x IR/4x RS232/8x Ethernet/4x I/O Sensor

Communication and Control

Ethernet	8x LAN - 8-pin RJ-45 female 10/100 Mbps auto-negotiating
IR	16x IR TX - 3.5mm (1/8in) TS Mono 1x IR IN - 3.5mm (1/8in) TRS Stereo 1x IR IN Sensor on Front Panel
RS-232	4x RS-232 - 9-pin DB9 Male
Relays	4x NO (Normally Open) Relays – Shared 24pin Phoenix 4x NC (Normally Closed) Relays - Shared 24pin Phoenix
Sensors	4x Sensors (12V) - Shared 24pin Phoenix
USB	1x USB Type A

Power

Power Supply	Input: 100~240V AC 50/60Hz
Max Power Consumption	5W

Environmental

Operating Temperature	32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing
Storage Temperature	-4°F to ~ 158°F (-20°C ~ +70°C) 10% ~ 90%, non-condensing
Maximum BTU	17.00 BTU/hr

Dimensions & Weight

Rack Units/Wall Box	1U
Height	42.3mm/1.67in
Width	440mm/17.33in
Depth	261.6mm/10.3in
Weight	3.74kg/8.23lbs

Regulatory

Safety and Emission	CE FCC RoHS
----------------------------	-----------------