

AG Neovo SX-15P 15in Display w Anti-Burn-in and NeoV technology for 24/7 control

Panel	Panel Type	LED-Backlit TFT LCD
	Panel Size	15.0"
	Max. Resolution	XGA 1024 x 768
	Pixel Pitch	0.297 mm
	Brightness	350 cd/m2 (Typkal)
	Contrast Ratio	700:1 (Typical)
	Viewing Angle (H/V)	170°/160° (Typical)
	Display Colour	16.7M
	Response Time	4 ms (GTG)
Horizontal Resolution	TV Lines	620TVL (NTSC), 625TVL (PAL)
Frequency (H/V)		H: 24 kHz-81 kHz
		V: 50 Hz - 75 Hz
Input	VGA	15-Pin D-Sub
	DVI	24-Pin DV1-D
	CVBS	BNCx2
	S-Video	4-Pin mini DIN
Output	CVBS	BNCx2
	DC Output	12V/500mA, DC jack 2.50
Audio	Audio In Audio Out Speaker	1 x stereo audio in for PC 1 x stereo audio in for CVBS (RCA)/ S-Video 1 x stereo audio out for CVBS (RCA)/ S-Video 1.5W x 2
Power	Power Supply Power Requirements Consumption	External DC 12V < 17 W (On) / < 0.5 W (Off)
NeoV™ Optical Glass	Thickness Reflection Rate Transmission Rate Coating Hardness	3.0 mm (0.18") <2% > 96% >8H
Plug & Play	VESA	DCC 2B, DCC/CI
Operating Conditions	Temperature Humidity	0°C - 40°C (32°F - 104°F) 10% - 90%
Storage Conditions	Temperature Humidity	-20°C - 60°C (-4°F - 140°F) 5% - 95%
Mounting	VESA FPMPI	Yes (100 x 100mm & 75 x 75mm)
Tilt		0° - +20°
Dimensions	Product (W x H x D) Packaging (W x H x D)	380x359x155 mm (15.0" x 14.1" x 6.1") 454x422x190 mm (17.9" x 16.6" x 7.5")
Weight	Product Weight	4.7kg (10.4lbs)
	Packaged Weight	6.3kg (13.9lbs)
Regulation Approval	Certifications & Compliance	CB, FCC, CE, WEEE, RoHS, REACH,
Accessories	Supplied	CD ROM (user manual), power cord, power adaptor, 15-Pin D-Sub cable, warranty card