

Audio and Video

Inputs	1x HDMI In 19-pin HDMI type A
Outputs	4x HDMI Out 19-pin HDMI type A
Video Encoding	NA
Encoding Data Rate	NA
End to End Latency	NA
Audio Formats	2ch PCM Multichannel: LPCM and Upto DTS-X and Dolby Atmos

Video Resolutions (Max)	Video Resolutions	HDMI
	1920x1080p @60Hz 12bit	15m/49ft
	1920x1080p @60Hz 16bit	7m/23ft
	3840x2160p @24Hz 10bit 4:2:0 HDR	5m/16ft
	3940x2160p @30Hz 8bit 4:4:4	7m/23ft
	3840x2160p @60Hz 10bit 4:2:0 HDR	5m/23ft
	4096x2160p @60Hz 8bit 4:2:0	7m/23ft
	4096x2160p @60Hz 8bit 4:4:4	5m/16ft

Supported Standards	DCI RGB HDR HDR10 Dolby Vision up 30Hz HLG BT.2020
----------------------------	--

Maximum Pixel Clock	600Mhz
----------------------------	--------

Communication and Control

HDMI	HDCP 2.2 EDID DVI-D supported with adapter (not included)
-------------	---

Power

Power Supply	5V DC 1A
Max Power Consumption	1.8W

Environmental

Operating Temperature	32°F ~ 113°F (0°C ~ 45°C) 10% ~ 90%, non-condensing
------------------------------	--

Storage Temperature	-4°F to ~ 158°F (-20°C ~ +70°C) 10% ~ 90%, non-condensing
----------------------------	--

Maximum BTU	6.14 BTU/hr
--------------------	-------------

Dimensions & Weight

Rack Units/Wall Box <1U

Height	20mm/0.79in
---------------	-------------

Width	140mm/5.5in
--------------	-------------

Depth	65.2mm/2.57in
--------------	---------------

Weight	0.24kg/0.53lbs
---------------	----------------

Regulatory

Safety and Emission	CE FCC RoHS RCM -4°F to ~ 158°F (-20°C ~ +70°C)
----------------------------	---
