

# Kramer KR-3000 Wired and Wireless Meeting Space Solution for 1-4 Participants

## VIA Connect PLUS - Wireless Presentation Solution

INPUTS	4 USB 3.0, 1 LAN on an RJ-45 connector, 1 HDMI
GRAPHIC OUTPUTS	1 HDMI, 1 mini DisplayPort Note: Does not support graphic output to both the HDMI and Mini Display Port simultaneously
AUDIO OUTPUT	1 3.5mm mini jack for headphones/speakers
MAX. RESOLUTION	For the HDMI Input: 1080p@60Hz
PROCESSOR	4th generation Intel® Dual core 1.4GHz
MAIN MEMORY	4GB, high speed
STORAGE	32GB, solid-state drive
LAN	Gigabit LAN
AUDIO	Analog or embedded HDMI, S/PDIF Realtek ALC269
POWER SUPPLY	65W power adapter (19V/3.4A)
INPUT VOLTAGE	100V-220V AC, 50/60HZ, auto sensing
INCLUDED ACCESSORIES	Power cord, Kramer HDMI Male to Female cable extender, VESA mounting bracket
PRODUCT DIMENSION	11.80cm x 11.50cm x 4.00cm (4.65" x 4.53" x 1.57" ) W, D, H
PRODUCT WEIGHT	0.5kg (1.1lbs) approx.

## VIAcast - Miracast Enabled USB Dongle for VIA Devices

STANDARDS COMPLIANCE	Standards: IEEE 802.11 a, 802.11 b, 802.11 g, 802.11 n, 802.11 ac Certifications: FCC, CE, IC, RoHS, WEEE, IDA, C-Tick, Wi-Fi A/B/G/N/AC
CONNECTOR	USB 3.0
USER INTERFACE	Indicator: Communication LED
ANTENNA	2 internal, dual-band
SECURITY FEATURES	Up to 128-bit encryption
OPERATING FREQUENCY RANGE (MHZ) 1	Low Frequency (MHz): 2400, High Frequency (MHz): 2483.5, Power (Watt): 0.1, Bandwidth (Khz): 40,000.00, Type of Modulation: OFDM
OPERATING FREQUENCY RANGE (MHZ) 2	Low Frequency (MHz): 5150, High Frequency (MHz): 5350, Power (Watt): 0.1, Bandwidth (Khz): 40,000.00, Type of Modulation: OFDM, DSSS
ENVIRONMENTAL CONDITIONS	Operating Temperature: 0° to +40°C (32° to 104°F)
	Storage Temperature: -20° to +70°C (-4° to 158°F)
	Operating Humidity: 10% to 85%, RHL non-condensing
	Storage Humidity: 5% to 90%, RHL non-condensing
PRODUCT DIMENSION	11.80cm x 11.50cm x 4.00cm (4.65" x 4.53" x 1.57") W, D, H

## C-MHM/MMH - Flexible High-Speed HDMI Cable with Ethernet

VIDEO	Max Resolution for 1-15ft (0.3-4.6m) lengths: 4K60Hz (4:4:4)
	Max Data Rate for 1-15ft (0.3-4.6m) lengths: 18Gbps (6Gbps per channel)
	HDMI Support: HDCP 2.2, EDID, CEC, HDR-10, HLG, Dolby Vision
AUDIO	Supported Audio Formats: Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio™, DVD Audio, SA-CD
PHYSICAL	Connectors: 2 Male HDMI Type A, 24K gold-plated with K-Lock
	Bending Radius: 58mm
CONDUCTORS	Diameter: 30AWG (7/0.1)
	Material: Tinned Copper
SCREENING	Type: Triple shielding
JACKET	Material: PVC
	Color: Gray, White
	Diameter: 5.8 ± 0.15mm
ELECTRICAL	Temperature Rating: 80°C
	Voltage Rating: 30V
	Conductor Resistance: 376.96Ω/KM MAX. at 20°C
	Rating (NEC/UL/CSA): VW-1/CMG-FT4

REGULATORY	RoHS: 2011/65/ EU
------------	-------------------

**PC5E-100 - CAT5E UTP 100MHz CM 4x2x24AWG Patch Cord**

CONSTRUCTION	Conductor Material: Annealed copper
	Conductor Diameter: 7x0.2 ±0.01 mm
	Insulation Material: HDPE
	Insulation Diameter: 0.97 ±0.08mm
	Color code: Blue/white blue, brown/white brown, orange/white orange, green/white green
	Sheath Material: PVC
	Sheath Color: Gray RAL 7046
ELECTRICAL	Sheath Diameter: 5.5±0.20mm
	Impedance: 1-100MHz 100±15Ω
	Max. Conductor DC Resistance: < 94.7Ω/km
PHYSICAL	Propagation Velocity: 68%
	Mechanical Characteristics: Bending radius - installed: 35mm, during installation: 45mm
	Connector Type: Snagless RJ-45 UTP CAT5E
	Wiring: EIA/TIA568B
REGULATORY	Contact Plating: Gold 50pm
	Compliant Standards - Electrical: EIA/TIA 568B, ISO/IEC 11801