



KRAMER

TECHNICAL SPECIFICATIONS

Inputs	4 HDMI: On female HDMI connectors
Outputs	2 HDMI: On female HDMI connectors
Ports	1 Ethernet: On an RJ-45 female connector 1 RS-232: On a 3-pin terminal blocks 1 USB: On a mini USB connector 8 Remote Selection Contact-Closure Switches: On 9 terminal block pins
Video	Max. Resolution: 4K@60Hz 4:4:4 Max. Data Rate: 18Gbps (6Gbps per graphic channel) Compliance: HDCP 2.2/1.4
User Interface	Control: Input selector, output mute, EDID capture, and panel lock buttons. DIP switch HDCP configuration Indicators: Switching, IR, and power LEDs
Power	Source: 5V DC Consumption: 2.5A
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RH non-condensing
STANDARDS COMPLIANCE	Safety: CE Environmental: RoHs, WEEE
Enclosure	Size: Half-19" 1U Type: Aluminum Cooling: Convection ventilation
Accessories	Included: Power adapter, rubber feet, IR remote control transmitter
PRODUCT DIMENSION:	21.46cm x 16.30cm x 4.36cm (8.45" x 6.42" x 1.72") W, D, H
PRODUCT WEIGHT:	1.0kg (2.1lbs) approx
SHIPPING DIMENSION:	35.10cm x 21.20cm x 7.20cm (13.82" x 8.35" x 2.83") W, D, H
SHIPPING WEIGHT:	1.6kg (3.5lbs) approx