## **TECHNICAL SPECIFICATIONS**

Inputs 1 HDMI: On a female HDMI connector

Outputs 1 HDMI: On a female HDMI connector

Ports 1 Ethernet: On an RJ-45 connector

1 RS-232: On a 3-pin terminal block

1 USB: On a female USB type-A connector

Video Content Protection: HDCP 1.4 / 2.2

Max. Resolution: 4K@60Hz (4:4:4)

User Interface Control: Manual ON and OFF buttons

Indicators: Display ON/OFF status, RS-232 communication and power LEDs

Power Source: 5V DC

Consumption: 580mA

Environmental Conditions

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

Accessories Included: Power adapter, bracket set

**PRODUCT** 

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

DIMENSION:

PRODUCT WEIGHT: 0.3kg (0.6lbs) approx

SHIPPING DIMENSION: 15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT: 0.8kg (1.8lbs) approx