

# A-NeuVideo ANI-MFAV Multi-Function 4k HDBaseT/HDMI/VGA Extender (Transmitter/Receiver) Kit up to 230ft/70m

- **Transmitter Inputs/Outputs:**
  - (2) HDMI IN Type A [19-pin female]
  - VGA [DB15 VGA female]
  - AUDIO IN [3.5mm Stereo Mini-jack]
  - RS-232/POWER [RJ45]
- **Transmitter Outputs:** HDBaseT™ Out [RJ45]
- **Receiver Inputs:**
  - HDBaseT™ In [RJ45]
  - MIC IN [Screw Terminal]
  - USB [USB A TYPE]
  - TCP/IP [RJ45]
- **Receiver Outputs:**
  - HDMI OUT Type A [19-pin female]
  - RS-232 [Screw Terminal]
  - RELAY [Screw Terminal]
  - AUDIO OUT [Screw Terminal]
  - 2x30watts@40ohms amplifier output [Screw Terminal]
- **HDMI Compliance:** HDMI 1.4
- **HDCP Compliance:** HDCP 1.4
- **Video Bandwidth:** 10.2 Gbps
- **Video Resolution:** up to 4K2K@30Hz,1080P@120Hz and 1080P 3D@60Hz
- **Color Space:** RGB, YCbCr 4:4:4, YCbCr 4:2:2
- **Color Depth:** 8/10/12-bit
- **HDMI Audio Formats:** LPCM 2/5.1/7.1CH, Dolby Digital, DTS 5.1, Dolby Digital+, Dolby TrueHD, DTS-HD Master Audio, Dolby Atmos, DTS:X
- **ESD Protection:** Human Body Model:
  - ±8kV (Air Discharge)
  - ±4kV (Contact Discharge)
- **Dimensions (WxDXH):** Transmitter: .4 x .375 x .13 in (115.9x114.3x38.7mm) / Receiver: .8 x .3 x .1 in (50x104x 30mm)
- **Weight:** Transmitter: .6 lb/305g / Receiver: 1.7 lb/758g
- **Housing:** Metal Enclosure
- **Color: Transmitter:** White / Receiver: Black
- **Operating Temperature:** 0°C-40°C/32°F-104°F
- **Storage Temperature:** -20°C-60°C/-4°F-140°F
- **Relative Humidity:** 20-90% RH (Non-condensing)
- **Power Consumption:** 75W (max)
- **Power Supply:** Input: AC100 - 240V 50/60Hz, Output: DC 24V/3.75A (US/EU standards, CE/FCC/UL certified)