



KRAMER

CLS-2LC/OM3

2 LC MM OM3 Fiber Optic Cable – Low
Smoke & Halogen Free



Kramer's CLS-2LC/OM3 is a high-quality, dual LC to dual LC, MM 50/125µm OM3, low smoke and halogen free fiber patch cable

FEATURES

Quality Construction - Multimode 50/125 µm OM3 optical fiber with 850nm operating wavelength. Sub-cables are color coded blue and orange and terminated with the LC connectors

Numerous Applications - Use these cables to connect Kramer extender products as well as for 10 Gigabit Ethernet applications

Standards Compliance - Complies with ITU-T G.651.1, TIA/EIA 492AAAC and IEC60793-2-10 A1a.2a standards

Varied Selection of Lengths - Available in versions of 33ft to 656ft (10m to 200m)



TECHNICAL SPECIFICATIONS

PHYSICAL	Connector-1: 2x LC Connector-2: 2x LC Core diameter: 50µm Cladding diameter: 125µm
Insertion loss:	10M:I.L≤0.3dB, 20M:I.L≤0.4dB, 23M:I.L≤0.4dB, 30M:I.L≤0.4dB, 50M:I.L≤0.5dB, 75M:I.L≤0.7dB, 100M:I.L≤1.0dB, 175M:I.L≤1.4dB, 200M:I.L≤1.5dB
Operating Wavelength:	850nm
JACKET	Diameter: 7.0±0.5mm Material: Low smoke & halogen free Color: Aqua
Environmental Conditions	Storage/Operating Temperature: -20 to +60°C:
Regulatory:	
Regulatory Compliance (Standards Compliance)	ITU-T G.651.1, TIA/EIA 492AAAC and IEC60793-2-10 A1a.2a standards.:



KRAMER

CONFIGURATIONS

CLS-2LC/OM3-33	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
CLS-2LC/OM3-66	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
CLS-2LC/OM3-98	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
CLS-2LC/OM3-164	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
CLS-2LC/OM3-246	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
CLS-2LC/OM3-328	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
CLS-2LC/OM3-558	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
CLS-2LC/OM3-656	2 LC (M)to 2 LC (M) MM OM3 Fiber Optic Cable - LSHF
