

Kramer VS-44H2A 4x4 4K HDR HDMI 2.0 HDCP 2.2 Matrix Switcher with Audio De-embedding

INPUTS

- 4 HDMI: On female HDMI connectors

OUTPUTS

- 4 HDMI: On female HDMI connectors
- 4 S/PDIF: On female RCA connectors
- 4 Balanced Stereo Audio: On 5-pin terminal block connectors

PORTS

- 1 USB: On a Mini female connector
- 1 RS-232: On a 9-pin D-sub connector
- 1 IR IN: On a 3.5mm mini jack
- 1 Ethernet: On an RJ-45 female connector

VIDEO

- Max. Resolution: 4K@60Hz 4:4:4
- Max. Data Rate: 18Gbps (6Gbps per graphic channel)
- Compliance: Supports HDMI 2.0/1.4, HDCP 2.2/1.4,

USER INTERFACE

- Front Panel: IN and OUT selection buttons
- Front Panel: OFF, ALL, STO, RCL EDID, LOCK buttons

POWER

- Source: 100–240V AC, 50/60Hz
- Consumption: 60VA

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RH non-condensing

STANDARDS COMPLIANCE

- Safety: CE
- Environmental: RoHs, WEEE

ENCLOSURE

- Size: 19" 1U
- Type: Aluminum
- Cooling: Fan

ACCESSORIES

- Included: Power cord, rack ears, remote control transmitter with batteries

PRODUCT DIMENSION

- 43.64cm x 23.72cm x 4.36cm (17.18" x 9.34" x 1.72") W, D, H
- 43.64cm x 18.30cm x 4.36cm (17.18" x 7.20" x 1.72") W, D, H

PRODUCT WEIGHT

- 2.0kg (4.5lbs) approx.
- 2.0kg (4.5lbs) approx.

SHIPPING DIMENSION

- 52.50cm x 33.00cm x 10.70cm (20.67" x 12.99" x 4.21") W, D, H
- 55.00cm x 27.60cm x 10.70cm (21.65" x 10.87" x 4.21") W, D, H

SHIPPING WEIGHT

- 2.9kg (6.5lbs) approx.
- 2.9kg (6.5lbs) approx.