

# ICRealtime ICR-B2732Z 2MP IP Indoor/Outdoor Mid Size Bullet Camera/2.7-12mm Lens/180ft Smart IR/POE

<b>Model</b>	ICR-B2732Z
<b>Camera</b>	
Image Sensor	1/2.9" 2 Megapixel progressive scan CMOS
Effective Pixels	1920(H)x1080(V)
Scanning System	Progressive
Electronic Shutter Speed	Auto/Manual, 1/(3)4~1/10000s
Min. Illumination	0.01Lux/F1.4 (Color), 0Lux/F1.4(IR on)
S/N Ratio	More than 50dB
Video Output	N/A
<b>Camera Features</b>	
Max. IR LEDs Length	196Ft (60m)
Day/Night	Auto(ICR)/Color/B/W
Backlight Compensation	BLC / HLC / DWDR
White Balance	Auto/Manual
Gain Control	Auto/Manual
Noise Reduction	3D
Privacy Masking	Up to 4 areas
<b>Lens</b>	
Focal Length	2.7mm~12mm
Max Aperture	F1.4
Focus Control	Auto
Angle of View	H: 95°~ 34°
Lens Type	Motorized/ Fixed Iris
Mount Type	Board-in Type
<b>Video</b>	
Compression	H.264+ / H.264
Resolution	1080P(1920 x 1080) / 1.3M(1280 x 960) / 720P(1280 x 720) / D1(704 x 576 / 704 x 480) / CIF (352 x 288/352 x 240)
Frame Rate	Main Stream - 1080P/960P/720P(1 ~ 30fps) Sub Stream - D1/CIF(1 ~ 30fps)
Bit Rate	H.264: 3K ~ 8192Kbps
<b>Audio</b>	
Compression	N/A
Interface	N/A
<b>Network</b>	
Ethernet	RJ-45 (10/100Base-T)
Wi-Fi	N/A
Protocol	IPv4/IPv6, HTTP, HTTPS, SSL, TCP/IP, UDP, UPnP, ICMP, IGMP, SNMP, RTSP, RTP, SMTP, NTP, DHCP, DNS, PPPOE, DDNS, FTP, IP Filter, QoS, Bonjour
Compatibility	ONVIF, CGI, PSIA
Max. User Access	20 Users
Smart Phone	iPhone, iPad, Android, Windows Phone
<b>Auxiliary Interface</b>	
Memory Slot	Micro SD, Max 128GB
RS485	N/A
Alarm	N/A
PIR Sensor Range	N/A

**General**

Power Supply	12VDC / PoE (802.3af)
Power Consumption	Max 14W
Working Environment	-22°F~+140°F (-30°C~+60°C), Less than 95% RH
Ingress Protection	IP67
Vandal Resistance	N/A
Dimensions	2.83" x 3.15" x 8.38"
Weight	1.43lb