

# AVPro Edge AC-CXWP-HDMO-70KIT 4K HDMI/HDBaseT Decora Wall Plate Extender (Transmitter/Receiver) Kit up to 70m/230ft

## AC-CXWP-HDMO-T

<b>VIDEO:</b>	
VIDEO RESOLUTIONS	UP TO 4K60HZ 4:2:0 & 4K30 4:4:4
VESA RESOLUTIONS	UP TO 2560X2048 (QSXGA)
HDR FORMATS/RESOLUTIONS	4K24 4:2:2 12 BIT. 4K24 4:2:0 10 BIT
COLOR SPACE	YUV (COMPONENT). RGB (CSC: REC. 601. REC. 709. BT2020. DCI. P3 D 6500)
CHROMA SUBSAMPLING	4:4:4, 4:2:2, 4:2:0 SUPPORTED
DEEP COLOR	UP TO 12 BIT (4K)
<b>AUDIO:</b>	
AUDIO FORMATS SUPPORTED HDMI	PCM 2.0 CH. LPCM 5.1 & 7.1. DOLBY DIGITAL. DTS 5.1. DOLBY DIGITAL PLUS. DOLBY TRUEHD. DTS-HD MASTER AUDIO. DTS-X. DOLBY ATMOS
<b>DISTANCE:</b>	
DISTANCE 1080P	100M (330 FEET)
DISTANCE 4K& HDR	70M (230 FEET WITH CAT6A/7)
<b>OTHER:</b>	
BANDWIDTH	10.2 GBPS
CEC	YES
HDCP	HDCP 2.2 AND EARLIER
<b>PORTS:</b>	
HDMI (INPUT)	TYPE A
HDBASET (OUTPUT TO RECIEVER)	RJ45
<b>ENVIRONMENTAL:</b>	
OPERATING TEMPRATURE	23 TO 125T (-5 TO 5TC)
STORAGE TEMPERATURE	-4 TO 140BF (-20 TO 60°C)
HUMIDITY RANGE	5-90% RH (NO CONDENSATION)
<b>POWER:</b>	
POWER CONSUMPTION (TOTAL)	8 WATTS (16.5 WHEN PAIRED)
POWER SUPPLY	INPUT: AC 100-240V - 50/60HZ OUTPUT: DC 5V2A (MINI USB)
<b>DIMENSIONS:</b>	
DIMENSIONS (SINGLE UNIT ONLY. TX OR RX ARE SAME) (LENGTH/WIDTH/HEIGHT) (TX OR RX EACH ALONE)	MM: 70X 65X31 INCH: 2.75 X 2.55X1.22 (WITHOUT WALL DECORA COVER)
WALL SPACE	SINGLE GANG
COMPATIBLE BOX TYPES	MUD RINGS. STUD MOUINT. CLAMP MOUNT. METAL & PLASTIC BOXES. LV BOXES
DIMENSIONS (PACKAGED LENGTH/WIDTH/HEIGHT) (KIT)	MM: 159 X 137 X 89 INCH: 6.25 X 5.375 X 3.5
WEIGHT (UNIT)	0.4LBS (0.18KG)
WEIGHT (PACKAGED)	0.5LBS (0.23K6)

## AC-EX70-UHD-R

Video Resolutions	Up to 4K60 4:2:0 & 4K30 4:4:4
VESA Resolutions	Up to 2560x2048 (QSXGA)
HDR Resolutions	4K24 4:2:2 12 bit, 4K24 4:2:0 10 bit
Color Space	YUV, RGB (CSC: Rec. 601, Rec. 709, BT2020, DCI, P3 D6500)
Chroma Subsampling	4:4:4, 4:2:2, 4:2:0 Supported
Deep Color	Up to 12 bit w/4K

Audio Formats Supported	PCM 2.0 Ch, LPCM 5.1 & 7.1, Dolby Digital, DTS 5.1, Dolby Digital Plus, Dolby TrueHD, DTS-HD Master Audio, Dolby Atmos
Distance 1080P	70M (230 Feet)
Distance 4K & HDR	40M (131 Feet) (Best results with CAT6a/7)
Bandwidth	10.2 Gbps
CEC	Yes
HDCP	HDCP 2.2 and Earlier
Operating Temperature	23 to 95°F (-5 to 35°C)
Storage Temperature	-4 to 140°F (-20 to 60°C)
Humidity Range	5-90% RH (No Condensation)
Power Consumption	7.5 Watts
Power Supply	Input: AC 100-240V ~ 50/60Hz Output: DC 48V .5A (Wall Version) Output: DC 48V .625A 92-piece (Table Top Version)
Dimensions (Unit Only Height/Depth/Width)	mm: 12 x 100 x 80 (Tx & Rx ea) inch: .47 x 3.93 x 3.15 (Tx & Rx ea)
Weight (Unit)	.45lbs/.20kg (Tx & Rx ea)
Weight (Packaged)	.8lbs/.36kg (Tx & Rx ea)
•Specifications subject to change without notice. Mass & dimensions are approximate	