## Auratone 5C Black with Amp Super Sound Cube/Passive Monitor/80-15000 Hz/Black (Pair) with A2-30 Amplifier

Frequency Response	80 Hz - 15 kHz
Impedance	8 ohms
Driver	4.5" full range
SPL	90 dB @ 1 W / 1 m
Cabinet	Sealed 5/8" MDF
Wattage	25 W RMS / 50 W peak
Dimensions	6.5 x 6.5 x 6.0" / 16.5 x 16.5 x 15.2 cm
Packaging Info	·
Package Weight	10.7 lb
Box Dimensions (LxWxH)	15.5 x 9.3 x 8.9"
Auratone A2-30 Amplifier For 2 5C Super Sound Cub	pes
THD + N	0.03% (At 1 kHz, 1 W, 8 Ohms, Both Channels Driven)
	0.05% (At 1 kHz, 30 W, 8 Ohms, Both Channels Driven)
Wattage	23 W + 23 W (At 1 kHz, 1% THD+N, Both Channels Driven)
Voltage Gain	20 dB
Crosstalk	At 1 kHz, +4 dBu, <70 dBu
Input Sensitivity	1.228 Vrms, +4 dBu
Frequency Response	20 Hz to 20 kHz (±0.4 dBu)
Signal to Noise Ratio	>100 dB
Controls	AC Power Switch on Back
LED Indicators	Power (Green) on Front
Power	115 to 230 VAC
Power Consumption (Idle)	6.4 W (120 VAC)
Fuse	T1.6 A, 120 VAC, 0.2 x 0.8" / 5.0 x 20.0 mm
Connectors	Input: XLR-F, Balanced, Pin 2 Hot
	Output: 5-Way Gold Binding Posts
Dimensions	1.8 x 6.7 x 7.1" / 45 x 170 x 180 mm
Weight	2.8 lb / 1.3 kg