

| | |
|----------------------------------|--|
| Network Connector: | RJ45 Neutrik® etherCON®-style |
| Digital Audio Ethernet Protocol: | Dante |
| Transmission Rate: | 100 Mbps |
| Sample Rates Supported: | 44.1 kHz, 48 kHz (default), 88.2 kHz, 96 kHz |
| Bit Depth Supported: | 24 bits |
| Audio Operating Level: | -20 dBFS = +4 dBu |
| Reference Level: | 0 dBFS = +24 dBu |
| Outputs (4): | XLR (male) |
| Output Level (operating): | +4 dBu nominal LINE level balanced; -45 dBu nominal MIC level (into 150 Ω) |
| Output Level (maximum): | +24 dBu LINE level |
| Output Impedance: | < 100 Ω balanced |
| Selector per output: | Mic/Line |
| Frequency Response: | 20 Hz to 20 kHz (± 0.5 dB) |
| THD+N: | < 0.1% (20 Hz to 20 kHz, +4 dBu/-20 dBFS); 0.015% at 1 kHz (typ) |
| Noise: | < -75 dB (below +4 dBu); < -95 (below +24 dBu) |
| Crosstalk: | Below Noise Floor (1 kHz, output to output); < -60 d5 dB (20 kHz) |
| Headroom above +4 dBu/-20 dBFS: | 20 dB |
| Indicators (3): | Ethernet Link and Speed (2, rear panel); Sync (front panel) |
| Ambient Operating Environment: | 0° C to 50° C |
| Power Requirement: | PoE Class 0, IEEE 802.3af, or 24 Vdc @ 150 mA, Ground-referenced |
| Specification Conditions: | Gain/Level: ± 1 dB |
| Dimensions: | 5.19" (13.18 cm) W; 1.68" (4.27 cm) H; 5.97" (15.16 cm) D |
| Package Type: | Cardboard Box |
| Package Dimensions: | 7 x 4.375 x 2.25 in. |
| Shipping Weight: | 1.77 lbs. |
| WEEE weight: | 1.525 lbs. |
| Tariff code: | 8517.18.0050 |