

INPUTS

2 Balanced Mono Mic / Line Level Source: On 3-pin terminal blocks

PORTS

1 Dante: On an RJ-45 connector

1 RS-232: On a 3-pin terminal block

USER INTERFACE

Control: Dante IP control matrix, Kramer Protocol 3000 via RS-232, audio input configuration DIP-switches, reset button

Indicators: Power, Dante network, input selection and digital operation LEDs

POWER

Source: 48V DC (PoE)

Consumption: 100mA

ENCLOSURE

Size: PicoTOOLS®

Type: Aluminum

Cooling: Convection ventilation

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

STANDARDS COMPLIANCE

Safety: CE

Environmental: RoHs, WEEE

PRODUCT DIMENSION

6.22cm x 5.18cm x 2.44cm (2.45" x 2.04" x 0.96") W, D, H

PRODUCT WEIGHT

0.1kg (0.3lbs) approx.

SHIPPING DIMENSION

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

0.2kg (0.5lbs) approx.
