

INPUTS

HDMI: On a female HDMI connector

OUTPUTS

HDMI: On a female HDMI connector

S/PDIF Digital Audio: On an RCA connector

Balanced Stereo Analog Audio: On a 5-pin terminal block connector

VIDEO

Bandwidth: Up to 18Gbps (6Gbps per graphic channel)

Max. Resolution: Up to 4K@60 (4:4:4)

HDMI Support: 4K@60Hz and ARC as specified in HDMI 2.0

Content Protection: Supports HDCP 2.2

AUDIO

Frequency Response: 20Hz to 20kHz @ +/-0.1dB

S/N Ratio: >90dB

THD+N: 0.004%

USER INTERFACE

Control: Setup DIP-switches for EDID mode, audio settings, analog audio amplification. Contact closure switch for:output mute

Indicators: Audio sources (IN and OUT), Audio output (DIG and ANALOG), and ON LEDs

POWER

Consumption: 5V DC, 370mA

Source: 5.2V DC, 4A

ENVIRONMENTAL CONDITIONS

Operating Temperature: 0° to +40°C (32° to 104°F)

Storage Temperature: -40° to +70°C (-40° to 158°F)

Humidity: 10% to 90%, RHL non-condensing

REGULATORY

Safety: CE,

Environmental: RoHs, WEEE

ENCLOSURE

Size: Tool

Type: Aluminum

Cooling: Convection ventilation

ACCESSORIES

Included: 1 Power adapter, 1 power cord and 1 bracket set per device

PRODUCT DIMENSION

12.00cm x 7.15cm x 2.44cm (4.72" x 2.81" x 0.96") W, D, H

PRODUCT WEIGHT

0.2kg (0.5lbs) approx.

SHIPPING DIMENSION

15.70cm x 12.00cm x 8.70cm (6.18" x 4.72" x 3.43") W, D, H

SHIPPING WEIGHT

0.7kg (1.5lbs) approx.
