



## RTBUS-25xl

Round Table Mount Multi-Connection  
Solution – Pneumatic Lid – 110mm Cut-Out

| VGA/UXGA - 15-pin HD | HDMI | Ethernet - RJ-45



The RTBUS-25xl is an elegant furniture-mounted, modular, round connection bus featuring a pneumatic mechanism for pneumatic lifting and smooth closing of its lid. It is easily installed into a table or podium top and its interface enables you to connect any equipment to systems installed in a room via pass-through connectors for PC, USB, stereo audio, HDMI, Ethernet and power.

NOTE: The power socket and power cord are purchased separately

### FEATURES

Inputs - 15-pin HD, USB, 3.5mm, HDMI, Ethernet

Cover - Pop-up pneumatic lid

Cutout Size (Mount Dimension) - 110mm diameter



## TECHNICAL SPECIFICATIONS

---

Ports	1 HDMI: On a female HDMI connector 1 VGA: On a 15-pin d-sub connector 1 Audio: On a 3.5mm mini jack 1 Ethernet: On an RJ-45 connector 1 USB: On a female USB type-A connector
PHYSICAL	Cutout Size 110mm diameter
Environmental Conditions	Operating Temperature: 0° to +40°C (32° to 104°F) Storage Temperature: -40° to +70°C (-40° to 158°F) Humidity: 10% to 90%, RHL non-condensing
Power	Power rating varies according to the location and the power socket assembly (purchased separately) installed in the tbus, as follows: Universal: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet USA: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet Germany and EU: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet Belgium and France: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet Italy: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet Australia: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet Israel: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet South Africa: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet Switzerland: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet England: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet Brazil: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet Fuse Rating: T 6.3A 250V
Accessories	Included: Mounting brackets Optional: TBUS AC Power Cord, power socket kits
Product Dimension	EU: 8.00cm x 4.70cm x 8.00cm (3.15" x 1.85" x 3.15" ) W, D, H UK: 8.60cm x 4.70cm x 8.60cm (3.39" x 1.85" x 3.39" ) W, D, H US: 6.98cm x 4.70cm x 11.43cm (2.75" x 1.85" x 4.50" ) W, D, H EU, UK: 8.00cm x 4.70cm x 8.00cm (3.15" x 1.85" x 3.15" ) W, D, H
Product Weight	EU: 0.1kg (0.2lbs) approx UK: 0.1kg (0.2lbs) approx US: 0.1kg (0.2lbs) approx EU, UK: 0.1kg (0.2lbs) approx
Shipping Dimension	EU: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H UK: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H

US: 11.50cm x 4.70cm x 7.00cm (4.53" x 1.85" x 2.76" ) W, D, H

EU, UK: 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94" ) W, D, H

Shipping Weight

EU: 0.4kg (0.8lbs) approx

UK: 0.4kg (0.8lbs) approx

US: 0.4kg (0.8lbs) approx

EU, UK: 0.4kg (0.8lbs) approx