

Kramer RTBUS-25XL Round Table Mount Multi-Connection Solution - Pneumatic Lid - 110mm Cut-Out

PORTS

- 1 HDMI: On a female HDMI connector
- 1 VGA: On a 15-pin d-sub connector
- 1 Audio: On a 3.5mm mini jack
- 1 Ethernet: On an RJ-45 connector
- 1 USB: On a female USB type-A connector

PHYSICAL

- Cutout Size: 110mm diameter

ENVIRONMENTAL CONDITIONS

- Operating Temperature: 0° to +40°C (32° to 104°F)
- Storage Temperature: -40° to +70°C (-40° to 158°F)
- Humidity: 10% to 90%, RHL non-condensing

POWER

- Power rating varies according to the location and the power socket assembly (purchased separately) installed in the tbus, as follows:
- Universal: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
- USA: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Germany and EU: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Belgium and France: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Italy: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Australia: 100-240V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Israel: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
- South Africa: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Switzerland: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
- England: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Brazil: 220V AC, 50/60Hz, 5A, maximum 5A per power outlet
- Fuse Rating: T 6.3A 250V

ACCESSORIES

- Included: Mounting brackets
- Optional: TBUS AC Power Cord, power socket kits

PRODUCT DIMENSION

- **US:** 6.98cm x 4.70cm x 11.43cm (2.75" x 1.85" x 4.50") W, D, H
- **EU, UK:** 8.00cm x 4.70cm x 8.00cm (3.15" x 1.85" x 3.15") W, D, H

PRODUCT WEIGHT

- **US:** 0.1kg (0.2lbs) approx.
- **EU, UK:** 0.1kg (0.2lbs) approx.

SHIPPING DIMENSION

- **US:** 11.50cm x 4.70cm x 7.00cm (4.53" x 1.85" x 2.76") W, D, H
- **EU, UK:** 23.20cm x 13.60cm x 10.00cm (9.13" x 5.35" x 3.94") W, D, H

SHIPPING WEIGHT

- **US:** 0.4kg (0.8lbs) approx.
- **EU, UK:** 0.4kg (0.8lbs) approx.