

VIDEO:	
VIDEO RESOLUTIONS	UP TO 4K 60HZ 4:2:0 & 4K30 4:4:4
VESA RESOLUTIONS	UP TO 2560X2048 (QSXGA)
HDR FORMATS/RESOLUTIONS	4K24 4:2:2 12 BIT, 4K24 4:2:0 10 BIT
COLOR SPACE	YUV (COMPONENT), RGB (CSC: REC. 601, REC. 709, BT2020, DCI, P3 D6500)
CHROMA SUBSAMPLING	4:4:4, 4:2:2, 4:2:0 SUPPORTED
DEEP COLOR	UP TO 16 BIT (1080), UP TO 12 BIT (4K)
AUDIO:	
AUDIO FORMATS SUPPORTED HDMI	PCM 2.0 CH, LPCM 5.1 & 7.1, DOLBY DIGITAL, DTS 5.1, DOLBY DIGITAL PLUS, DOLBY TRUEHD, DTS-HD MASTER AUDIO, DTS-X, DOLBY ATMOS
AUDIO FORMATS SUPPORTED EXTRACTED (TOSLINK)	PCM 2.0 CH, LPCM 6CH, LPCM 7CH, DOLBY DIGITAL, DOLBY DIGITAL PLUS, DTS MASTER AUDIO
AUDIO FORMATS SUPPORTED EXTRACTED (2CH)	PCM 2CH
DISTANCE:	
HDMI LEAD IN/OUT (4K60 4:4:4)	UP TO 50 FEET (USING BULLET TRAIN HDMI)
HDMI LEAD IN/OUT (W/ AOC CABLE) (4K60 4:4:4)	UP TO 2130 FEET (USING BULLET TRAIN AOC)
HDBASET (CAT) DISTANCE 1080P	100M (330 FEET) (WITH CAT 6A/7)
HDBASET (CAT) DISTANCE 4K & HDR	70M (230 FEET) (WITH CAT6A/7)
OTHER:	
BANDWIDTH (HDMI)	18 GBPS
BANDWIDTH (HDBT)	10.2 GBPS (18GBPS W/ICT AND AC-EX70-444-RNE)
HDCP	HDCP 2.2 AND EARLIER
PORTS:	
HDMI (INPUT)	TYPE A
HDBASET (INPUT)	RJ45
AUDIO (EXTRACTED DIGITAL)	TOSLINK
AUDIO (EXTRACTED ANALOG)	BALANCED L/R AUDIO (5 PIN TERMINAL BLOCK)
IR	3.5MM IR IN/OUT AND IR WINDOW ON THE FRONT
RS232	3 PIN TERMINAL BLOCK
CONTROL:	
PORTS	LAN, RS232, IR WINDOW
LAN WEBOS	YES
ENVIRONMENTAL:	
OPERATING TEMPRATURE	23 TO 125°F (-5 TO 51°C)
STORAGE TEMPERATURE	-4 TO 140°F (-20 TO 60°C)
HUMIDITY RANGE	5-90% RH (NO CONDENSATION)
POWER:	
POWER CONSUMPTION (TOTAL)	12 WATTS MAX
POWER SUPPLY	INPUT: AC 100-240V ~ 50/60HZ OUTPUT: DC 48V 0.5A
DIMENSIONS:	
DIMENSIONS (UNIT ONLY LENGTH/DEPTH/HEIGHT)	MM: 220.7 X 158.8 X 41.4 INCH: 8.69 X 6.25 X 1.63
DIMENSIONS (PACKAGED LENGTH/DEPTH/HEIGHT)	MM: 397 X 222 X 95.3 INCH: 15.63 X 8.75 X 3.75
WEIGHT (PACKAGED)	3.4 LBS (1.54 KG)

*SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE. MASS & DIMENSIONS ARE APPROXIMATE