

## Bosch DCNM-APS2 DICENTIS Audio Powering Switch/Second Generation

Supply voltage	100-240 Vac 50-60 Hz
Power consumption	530 W
System supply	48 Vdc
Total power supply	3x 144 W + 15 W
Frequency response	30 Hz - 20 kHz
THD at nominal level	< 0.1 %
Dynamic range	> 95 dB
Signal-to-noise ratio	> 95 dB
XLR nominal input	-18 dBV (+6 dB / -18 dB)
XLR maximum input	+18 dBV
Cinch nominal input	-30 dBV (+6 dB / -18 dB)
Cinch maximum input	+6 dBV
XLR nominal output	-18 dBV (+8 / -24 dB)
XLR maximum output	+20 dBV
Cinch nominal output	-30 dBV (+8 / -24 dB)
Cinch maximum output	+8 dBV
Mounting	Tabletop or mounted in a 19" rack
Dimensions (H x W x D)	
for tabletop use, with feet:	92 x 440 x 400 mm(3.6 x 17.3 x 15.7 in)
for 19" rack use, with brackets:	88 x 483 x 400 mm(3.5 x 19 x 15.7 in)
in front of brackets	40 mm (1.6 in)
behind brackets	360 mm (14.2 in)
Weight	7.62 kg (16.79 lbs)
Color	Traffic black RAL 9017Pearl light grey RAL 9022
Operating temperature	0 °C to +45 °C(-32 °F to +113 °F)
Storage and transport temperature	-20 °C to +70 °C(-4 °F to +158 °F)
Relative humidity	< 96 %, > 5 %