

**Soundtube CM1001d-T-BK 10in IN-CEILING SUBWOOFER/55 Hz - 118 Hz/Black**

System Type	10-inch subwoofer, in-ceiling, ported (150-watt transformer for 25/70.7/100-volt or transformer bypass)
Impedance (nominal) <sup>1</sup>	4 ohm
Sensitivity dB @ 2.83 V/1 m	92.0 dB
Sensitivity dB @ 1 W/1 m <sup>2</sup>	89.0 dB
Frequency Response (-3 dB) <sup>3</sup>	55 Hz-118 Hz
Frequency Response (-10 dB) <sup>3</sup>	41 Hz-224 Hz
Max. Program Power <sup>4</sup>	300 w
Max. Continuous Power RMS <sup>4</sup>	150w
Max. Power SPL @ 1 m <sup>0</sup>	111.0 dB
Low-Frequency Driver	254 mm (10 in.) Polypropylene cone, butyl rubber surround
Low-Frequency Voice Coil	35.0 mm (1.38 in.)
Crossover Frequency	100 Hz
Low-Pass Filter	6 dB per octave, 1st order
Enclosure Material	Drawn steel backcan with ABS baffle
Motor Board	N/A
Grille	Powder coated steel with integrated ABS baffle
Inputs	Four-pin, 5.08 mm Euroblock for individual or daisy chain connection
Colors	Black or white
Backcan Height	316.5 mm (12.46 in.)
Visible Diameter	374.9 mm (14.76 in.)
Visible Height	27.4 mm (1.08 in.)
Mounting Hole Diameter	323.9 mm (12.75 in.)
Min. Ceiling Thickness	6.4 mm (0.25 in.)
Max. Ceiling thickness	48.5 mm (1.91 in.)
Weight	12.3 kg (27.0 lb.)
Shipping Weight	14.5 kg (32.0 lb.)
Included accessories	Tile bridge, Euroblock connector, paint mask, restraint cable
Optional accessories	Pre-construction bracket (AC-CM8PCB), junction box (AC-CM-JBOX)
Packaging	One per box
Regulatory-CE	Approved
Regulatory - UL	UL 1480 (UEAY) and 2043 Approved
RoHS	Approved