

Bolide BC1209/PTZMINI/AH 1080P 10x Optical Zoom Mini PTZ Camera/IP66/12VDC

| Specifications | |
|-----------------------|---|
| Sensor | 1/3" Sony 322 CMOS Sensor+NVP2441H |
| Min. Illumination | Color: 0.5 lux, BW: 0.1lux |
| Resolution | 1080p / 720p |
| OPTICS | Optical x10 Zoom f= 5.5mm - 55mm |
| Angle | Approximate 55.2° (Wide) to 3.2° (Tele) |
| S/N (Y signal) | 52dB |
| White Balance | Auto |
| Manual speed | Pan (0.1°~200°/S) Tilt (0.1°~180°/S) |
| ICR | Manual/Auto |
| DNR | Auto / Off / Low / Middle / High |
| HLC | Off / On |
| Max Gain | Auto |
| Iris | Auto |
| Flip | Vertical, Horizontal, Vertical-Horizontal, OFF Selectable |
| Rotation | Pan continuously 360°, tilt 0~90° with auto-flip |
| Preset | 128 preset, title can be edited |
| Auto-flip | Tilt down 90°, with auto-flip 180° |
| Scan | 355° programmable, 4 scan |
| Pattern | 4 patterns, and each record time is not less than 180s |
| Tour | 4 tour and speed & park time of presets can be set. |
| Remote controlling | RS485 |
| Baud rate (RS485) | 2400 / 4800 / 9600/19200 bps |
| ID range | 1-254(software add.) |
| Output | AHD |
| Protocols | Pelco D, Pelco P |
| Electrical | |
| Input Voltage | DC 12V, 2 AMP |
| Power consumption | 9W/25W (IR_LED ON) |
| Operating Temperature | -10°C ~ +50°C |
| Physical | |
| Size | 8in x 8.5in |
| Net Weight | 4 Lbs. |
| IP Standard | IP66 |