

Induction Dynamics ID1 6.5 inch 3-Way/4-Way Speaker with Dual 10 inch Subwoofers/Pair

	Upper	Lower
Crossover Frequencies	80 (switchable), 700, 3,800 Hz	80 Hz (switchable)
Crossover Type	S4X™ 4th Order	S4X™ 4th Order
Nominal Impedance	8 Ω	4 Ω
Frequency Response	60 - 22,000 Hz	25 - 150 Hz
Sensitivity (2.83V @ 1M)	89 dB	89 dB
SPL (1W/1M)	89 dB	86 dB
Power Handling (RMS)	150 W	800 W
Magnetic Shielding	Yes	No
Enclosure	Ported	Vented
Tweeter	1.125" titanium inverted dome	
Midrange	3" soft dome	
Woofer	6.5" kevlar cone with rubber surround & cast frame	
Subwoofer	Dual 10" mica-graphite poly cone with cast frames and rubber surrounds	
Binding Posts	Gold-plated; #2 AWG wire	
Dimensions	56" H x 11" W x 10.5" D	
Weight	85 lbs	
Standard Finish Options	Black Gloss and Black Satin	
Grille	Fabric-covered, non-reflective frame; 63 standard color options	
Optional Accessories	A2 Subwoofer Amplifier	