

Induction Dynamics ID1.iw 6.5 inch 4-Way In-Wall Speaker with Dual 10 inch Subwoofers/Pair

	Upper	Lower
Crossover Frequencies	700; 3,800 Hz	Active Only
Crossover Type	S4X™ 4th Order	S4X™ 4th Order
Nominal Impedance	8 Ω	4 Ω
Frequency Response	55 - 22,000 Hz	27 - 150 Hz
Sensitivity (2.83V @ 1M)	90 dB	80 dB
SPL (1W/1M)	90 dB	77 dB
Power Handling (RMS)	150 W	500 W
Magnetic Shielding	Yes	No
Enclosure	Ported	Vented
Tweeter	1.125" inverted titanium dome	
Midrange	3" soft dome	
Woofer	6.5" made with Kevlar® cone with rubber surround & cast frame	
Subwoofer	(2) 10" shallow-mount drivers with rubber surrounds	
Binding Posts	Nickel-plated; #8 AWG wire	
Dimensions	54.5" H x 13.5" W x 4.5" D	
Cutout Dimensions	53.125" H x 12.5" W	
Weight	56 lbs.	
Standard Finish Options	Black Gloss and Black Satin	
Grille	Fabric-covered, non-reflective frame; 63 standard color options	
Optional Accessories	A2 Subwoofer Amplifier	