Icron 2301 USB 2.0 Ranger 1-Port Extender (Transmitter/Receiver) Set over CAT 5e/6/7 up to 100m

RANGE

• Direct connect up to 100m (330 ft) over CAT 5e/6/7

SPEEDS

- USB 2.0: up to 480 Mbps
- USB 1.1: up to 12 Mbps

LEX (Local Extender)

- USB Connector: 1 x USB Type B Receptacle
- Link Connector: 1 x RJ45
- Dimensions: 86.0mm x 75.0mm x 26.0mm (3.4" x 3.0" x 1.0")
- Mounting: Slots for cable ties or optional mounting kit available
- Enclosure Material: Silver anodized aluminium

REX (Remote Extender)

- USB Connector: 1 x USB Type A Receptacle
- Link Connector: 1 x RJ45
- Available Current: up to 1 Amp to USB port
- Power Supply: 100-240V AC Input, 5V 3A DC Output
- Dimensions: 86.0mm x 75.0mm x 26.0mm (3.4" x 3.0" x 1.0")
- Mounting: Slots for cable ties or optional mounting kit available
- Enclosure Material: Silver anodized aluminium

ENVIRONMENTAL

- Operating Temperature: 0C to 50C (32F to 122F)
- Storage Temperature: -20C to 70C (-4F to 158F)
- Operating Humidity: 20% to 80% relative humidity, non-condensing
- Storage Humidity: 10% to 90% relative humidity, non-condensing

COMPLIANCE

- EMC: FCC (Class B), CE (Class B)
- Environmental: RoHS2, REACH, Conflict Minerals

SUPPORT

• Warranty: 2-year