Adder AVSD1002-US 2-Port Secure USB DVI-I EAL2/KVM Switch

Video

- Analog: up to 1920 x 1200 x 60Hz
- Single link digital: up to 1600 x 1200 x 60Hz
- Dual link digital: up to 2560 x 1600 x 60Hz

Hardware compatibility

• Supports PC, Sun, Apple, RS/6000, Alpha and SGI-computers with USB keyboard and mouse interfaces and either VGA or DVI video interfaces.

O/S Compatibility

• All known software and operating systems including Windows (all), DOS, Linux, Unix, BSD, Sun OS, Solaris, Mac OS, NetWare etc.

Computer connections

• Video: DVI-I, Keyboard/Mouse: USB type B, Audio: 3.5mm stereo jack

KVM console

• Video: DVI-I, Keyboard/Mouse: USB type A , Audio: 3.5mm stereo jack

Physical design

• 234mm / 9.2"(w) x 140mm / 5.5"(d) x 44mm / 1.7"(h) 1.4kgs / 3 lbs

Power

• 100 - 240VAC, 50-60Hz, 10W

Operating temperature

• 0 to 40 deg C / 32 to 104 deg F

Approvals

- CE, FCC
- Order Codes

AVSD1002-US: Secure Switch with USB and DVI, 2 port

Optional Accessories

RMK3: 19 inch Rackmount kit (234mm wide, 1U products)