Video	
Standards Input Port Output Port Video Resolutions 3D Format Color Space Color Depth Bandwidth	HDMI 2.0, HDCP 2.2 1 x HDMI Type A [19-pin female] 4 x HDMI Type A [19-pin female] Up to 4Kx2K @ 60 Hz (4:4:4 3840x2160 @ 60 Hz) 1080P @ 60 Hz. RGB, YCbCr 4:4:4, YCbCr 4:2:2, YCbCr 4:2:0 30/36/48 Single-link to 340 MHz (10.2 Gbps)
Audio	
Supported Formats	LPCM 7.1, Dolby TrueHD, DTS-HD Master Audio, DTS, Dolby-AC3, DSD
General	
Power Supply Max Power Consumption Temperature/humidity Enclosure type ESD Protection Dimensions (W x D x H) Weight	12 vDC, 1 ADC (with universal AC plug kit) 10 W (Max) Storage: -20~60 °C / -4~140 °F Operating: 0~50 °C / 32~122 °F Relative Humidity: 20~90% RH (Non-condensing) Metal Human Body model: 8 kV (air-gap discharge) & 4 kV (contact discharge) 7.56 x 3.31 x 0.98 inch (84 x 192 x 25 mm) Model - 1.65 lbs (0.75 kg) Shipping – 2.3 lbs (1.04 kg)