

Size	24"
Resolution	3840 x 2160 (16:9)
Pixel Pitch	0.137mm
Color Depth	1.07B (10bit)
Viewing Angle (Typ.)	178°(H)/178°(V)
Luminance (Max.)	500cd/m ²
Contrast Ratio	1200:1
Display Area	526(H)X296(V)mm

Input

4 x BNC	12G-SDI A/B Channel Input, 3G-SDI C/D Channel Input
1 x HDMI	HDMI Input (HDMI 2.0)

Output

4 x BNC	12G-SDI A/B, 3G-SDI C/D Channel (Loop Through Out)
---------	---

Input Signal

12G-SDI	12Gb/s
6G-SDI	6Gb/s
3G-SDI	2.970Gb/s
HD-SDI	1.485Gb/s
HDMI	480p / 720p / 1080p / 2160p

SDI Input Signal Formats

SMPTE ST 2082	3840x2160 (60/50/59.94p)
SMPTE ST 2081	3840x2160 (30/25/24p/23.98p/29.97p)
SMPTE-425M-A/B	1080p(60/59.94/50/30/29.97/25/24/23.98/ 30sF/29.97sF/25sF/24sF/23.98sF)
SMPTE-274M	1080i(60/59.94/50)
	1080p(30/29.97/25/24/24sF/23.98/23.8sF)
SMPTE-296M	720p(60/59.94/50)
SMPTE-125M	480i(59.94)
ITU-R BT.656	576i(50)
Audio IN	Analog stereo
Audio OUT	Analog Stereo (Phone Jack)
Power	DC 12V / 24V / AC 100~240V(50~60Hz)
Power Consumption (Approx.)	TBD
Operating Temperature	0°C to 35°C (32°F to 95°F)
Storage Temperature	-20°C to 60°C (-4°F to 140°F)
Basic Accessory	AC Power Cable / Stand